

Guild Sewing Case

Fabric Requirements 3 fat quarters or 2/3 yard

(I used three different colors)

1. 7.5 x 17" back and part of flap
2. 7.5 x 17" Lining
3. 7.5 x 16 " lining/back pocket
4. 7.5 x 13" lining /middle pocket
5. 7.5 x 10" front lining /pocket

Batting 1. 7.5 x 17" (some have used fusible batting)

2. 7.5 x 5"

Velcro 1. 1" x 3.5" (cut in two)

Step 1. Lay the 7.5 x 10 front pocket rectangle on ironing mat wrong side up. Place the 7.5 x 5 batting at one end. Fold the remaining fabric over the top of the batting forming the 7.5 x 5 front pocket.

Step 2. Top edge $\frac{1}{4}$ " seam from the folded edge of pocket. Center one side of Velcro on edge of top stitching. Sew around Velcro through all layers.

Step 3. Fold the back and the middle rectangles wrong sides together. Top stitch $\frac{1}{4}$ " from fold.

Step 4. Layer the middle and front pockets. Pin. With a pencil draw a stitching line through the center of the front and middle pockets only at $3\frac{3}{4}$ " and 2" from edge of pocket.

Step 5. Sew on the stitching lines attaching the middle and front pocket to the back pocket.

Step 6. Layer batting, lining right side up and pocket unit with Velcro facing up. Place back flap rectangle right side down. Pin to hold all layers in place

Guild Sewing Case (con't)

Step 7. With $\frac{1}{4}$ " seam allowance sew around case leaving 3" opening along one side of the flap. Turn the case right side out through the opening(Trim $\frac{1}{4}$ " off each corner before sewing for easy corners).

Step 8. Starting at the edge of the pocket around and ending at the opposite side above the pocket, top stitch as close to the edge of the flap as you can.

Step 9. Center the Velcro on the inside lining $\frac{1}{4}$ " from edge. Sew on Velcro.

Step 10. You now have a case ready to use.

You can enlarge this to suit your needs.

I will bring a couple in different stages. If desired, bring your camera to take pictures.